

## Garant

### Side lock arbor Form AD with cooling channel bores, BT 30 short, Clamping $\varnothing$ D1: 10 mm



#### Order data

Order number	302593 10
GTIN	4045197944559
Item class	31A

#### Description

##### Version:

All shanks hard turned (for smooth running). Balancing quality G2.5 / 25,000 rpm. **With coolant supply holes that can be plugged.**

##### Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

##### Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 50 mm

External  $\varnothing$  D: 35 mm

Spare clamping screw No. 30 9900: 10

#### Technical description

Spare clamping screw No. 30 9900	10
External $\varnothing$ D	35 mm
Overhang dimension A	50 mm
Adapter	BT 30 short
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339

Shape	AD
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

Spare clamping screw for chucks with clamping $\varnothing$ D1 10 mm	309900 10
--	-----------