

**Garant**
**Side lock arbor Form AD with cooling channel bores, BT 30 short, Clamping Ø D1: 12 mm**

**Order data**

Order number	302593 12
GTIN	4045197944566
Item class	31A

**Description**
**Version:**

All shanks hard turned (for smooth running). Balancing quality G2.5 / 25,000 rpm. **With coolant supply holes that can be plugged.**

**Application:**

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

**Optional extras:**

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 55 mm

External Ø D: 42 mm

Spare clamping screw No. 30 9900: 12

**Technical description**

Spare clamping screw No. 30 9900	12
External Ø D	42 mm
Overhang dimension A	55 mm
Adapter	BT 30 short
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339

Shape	AD
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

Spare clamping screw for chucks with clamping Ø D1 12 mm	309900 12
--	-----------