



## Side lock arbor Form AD, BT 30 short, Clamping range $\varnothing$ D1: 10 mm



### Order data

Order number	302595 10
GTIN	4250122697930
Item class	36E

### Description

#### Version:

All shanks burnished.

#### Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

#### Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 50 mm

External  $\varnothing$  D: 35 mm

Spare clamping screw No. 30 9900: 10

### Technical description

Spare clamping screw No. 30 9900	10
Overhang dimension A	50 mm
Clamping $\varnothing$ D <sub>1</sub>	10 mm
External $\varnothing$ D	35 mm
Adapter	BT 30 short
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339

Shape	AD
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud 45° sealed suitable for steep tapers 30	308765 30
Pull stud 60° sealed suitable for steep tapers 30	308785 30
Pull stud 45° sealed suitable for steep tapers 30	308760 30
Spare clamping screw for chucks with clamping Ø D1 10 mm	309900 10