



Side lock arbor Form ADB with cooling channel, BT 40 A = 100, Clamping range \varnothing D1: 16 mm



Order data

| | |
|--------------|---------------|
| Order number | 302615 16 |
| GTIN | 4250122613039 |
| Item class | 36E |

Description

Version:

Coolant channel bore can be plugged with an O-ring.
All shanks burnished.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

External \varnothing D: 48 mm

Spare clamping screw No. 30 9900: 16

Technical description

| | |
|---------------------------------------|---------------|
| Clamping \varnothing D ₁ | 16 mm |
| Spare clamping screw No. 30 9900 | 16 |
| External \varnothing D | 48 mm |
| Adapter | BT 40 A = 100 |
| Standard | DIN 6359 |
| Arbor standard | ISO 7388-2 |
| Arbor standard | JIS B6339 |

| | |
|---------------------------------------|---------------------|
| Shape | ADB |
| Balance quality G at rotational speed | G 6.3 at 15,000 rpm |
| Concentricity | ≤ 3 μm |
| Machining strategy | HPC |
| Type of product | Side lock arbor |

Accessories

| | |
|--|-----------|
| Pull stud Hurco 60° with fit sealed suitable for steep tapers 40 | 308804 40 |
| Wrench for pull studs ISO 7388 suitable for ISO taper size 40 | 308830 40 |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40 | 308810 40 |
| Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40 | 308805 40 |
| Pull stud 60° sealed suitable for steep tapers 40 | 308785 40 |
| Pull stud Hurco 45° with fit sealed suitable for steep tapers 40 | 308802 40 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40 | 308820 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308795 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308760 40 |
| Pull stud 45° sealed suitable for steep tapers 40 | 308765 40 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40 | 308812 40 |
| Pull stud Hurco 90° with fit sealed suitable for steep tapers 40 | 308806 40 |
| Pull-stud 60° sealed suitable for steep tapers 40 | 308780 40 |
| Pull stud 90° sealed suitable for steep tapers 40 | 308790 40 |
| Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40 | 308803 40 |

Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40

308801 40

Spare clamping screw for chucks with clamping Ø D1 16 mm

309900 16