



Side lock arbor Form ADB, BT 50 short, Clamping range \varnothing D1: 32 mm



Order data

Order number	302660 32
GTIN	4250122615859
Item class	36E

Description

Version:

All shanks burnished.

Application:

For clamping tools with side flats to DIN 1835 B and DIN 6535 HB.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Overhang dimension A: 105 mm

External \varnothing D: 72 mm

Spare clamping screw No. 30 9900: 32

Technical description

Overhang dimension A	105 mm
Spare clamping screw No. 30 9900	32
Clamping \varnothing D ₁	32 mm
External \varnothing D	72 mm
Adapter	BT 50 short
Standard	DIN 6359
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339

Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50	308820 50
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50	308810 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50	308812 50
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Wrench for pull studs ISO 7388 suitable for ISO taper size 50	308830 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Spare clamping screw for chucks with clamping Ø D1 32 mm	309900 32