



Combination face mill adapter Form ADB, BT 50 A = 100, Spigot Ø d1: 40 mm



Order data

Order number	302965 40
GTIN	4250122616061
Item class	36E

Description

Version:

Taper shank, spigots, and contact surfaces ground on collar.
All shanks burnished.

Application:

With drive key for face mills with longitudinal slot, e.g. DIN 841.

With drive ring for face mills with crosswise slot DIN 1880 and cutter heads DIN 1830.

Supplied with:

Drive key, face mill drive ring, and lock screw.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Special toggle spanner No. 309840.

Note:

Internal cooling available only with suitable tightening screw No. 309861.

External Ø D: 70 mm

Spare milling cutter lock screw No. 309860: 40

Spare drive ring No. 309870: 40

Suitable toggle spanner No. 309840: 40

Technical description

Spare milling cutter lock screw No. 309860	40
Spare drive ring No. 309870	40
Spigot Ø d ₁	40 mm
Suitable toggle spanner No. 309840	40
External Ø D	70 mm

Adapter	BT 50 A = 100
Standard	DIN 6358
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	ADB
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling cutter spigot

Accessories

Pull stud 45° sealed suitable for steep tapers 50	308765 50
Milling cutter lock screw for mandrel Ø 40 mm	309860 40
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Toggle spanner for mandrel Ø 40 mm	309840 40
Face mill drive ring for mandrel Ø 40 mm	309870 40
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50