



## Face mill arbor with cooling channel bore form ADB, BT 40 short, Spigot $\varnothing$ d1: 40 mm



### Order data

Order number	303020 40
GTIN	4250122614227
Item class	36E

### Description

#### Version:

Taper shank, spigots, and contact surfaces ground on collar.  
All shanks burnished.

#### Supplied with:

Lock screw

#### Optional extras:

Pull studs (PS) No. 308760 – 308806. Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External  $\varnothing$  D: 88 mm

Spare milling cutter lock screw No. 309860: 40

### Technical description

Spare milling cutter lock screw No. 309860	40
Spigot $\varnothing$ d <sub>1</sub>	40 mm
Suitable toggle spanner No. 309840	40
Overhang dimension A	50 mm
External $\varnothing$ D	88 mm
Adapter	BT 40 short
Standard	DIN 6357

Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	ADB
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 6.3 at 15,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Milling head arbor

## Accessories

Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Milling cutter lock screw for mandrel Ø 40 mm	309860 40
Toggle spanner for mandrel Ø 40 mm	309840 40

