

**Garant**
**Face mill arbor vibration damped, BT 40 A = 200, Spigot Ø d1: 22 mm**

**Order data**

Order number	303050 22
GTIN	4045197821638
Item class	31A

**Description**
**Version:**

- **Plain shank.**
- **Taper shank, spigot, and all contact surfaces are ground at the collar.**
- **With Balluffchip bore.**
- **Larger collar contact face..**
- **Vibration damped version, arbor with vibration-damping core.**

**Advantage:**

Significantly lower tendency to vibrate. Considerable increase in feed rate.

**Supplied with:**

Cutter lock screw and drive dog.

**Optional extras:**

Special toggle spanner No. 309840.

**Note:**

Further sizes on request.

External Ø D: 48 mm

Milling mandrel length L<sub>4</sub>: 19 mm

**Technical description**

External Ø D	48 mm
Spigot Ø d <sub>1</sub>	22 mm
Milling mandrel length L <sub>4</sub>	19 mm
Adapter	BT 40 A = 200
Standard	DIN 6357

Arbor standard	DIN 69893
Arbor standard	JIS B6339
Arbor standard	JIS B6339
Shape	A
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor

## Accessories

Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Toggle spanner for mandrel Ø 22 mm	309840 22
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40

