

Garant
Face mill arbor vibration damped, BT 50 A = 300, Spigot Ø d1: 16 mm

Order data

Order number	303055 16
GTIN	4045197821706
Item class	31A

Description
Version:

- **Plain shank.**
- **Taper shank, spigot, and all contact surfaces are ground at the collar.**
- **With Balluffchip bore.**
- **Larger collar contact face..**
- **Vibration damped version, arbor with vibration-damping core.**

Advantage:

Significantly lower tendency to vibrate. Considerable increase in feed rate.

Supplied with:

Cutter lock screw and drive dog.

Optional extras:

Special toggle spanner No. 309840.

Note:

Further sizes on request.

External Ø D: 38 mm

Milling mandrel length L₄: 17 mm

Technical description

External Ø D	38 mm
Milling mandrel length L ₄	17 mm
Spigot Ø d ₁	16 mm
Adapter	BT 50 A = 300
Standard	DIN 6357

Arbor standard	DIN 69882-3
Arbor standard	JIS B6339
Arbor standard	JIS B6339
Shape	A
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
Pull-stud 60° sealed suitable for steep tapers 50	308780 50
Pull stud 60° sealed suitable for steep tapers 50	308785 50
Pull stud 90° sealed suitable for steep tapers 50	308795 50
Pull stud 90° sealed suitable for steep tapers 50	308790 50
Pull stud 45° sealed suitable for steep tapers 50	308760 50
Pull stud 45° sealed suitable for steep tapers 50	308765 50