

Garant
Face mill arbor vibration damped, BT 50 A = 300, Spigot Ø d1: 32 mm

Order data

| | |
|--------------|---------------|
| Order number | 303055 32 |
| GTIN | 4045197821737 |
| Item class | 31A |

Description
Version:

- **Plain shank.**
- **Taper shank, spigot, and all contact surfaces are ground at the collar.**
- **With Balluffchip bore.**
- **Larger collar contact face..**
- **Vibration damped version, arbor with vibration-damping core.**

Advantage:

Significantly lower tendency to vibrate. Considerable increase in feed rate.

Supplied with:

Cutter lock screw and drive dog.

Optional extras:

Special toggle spanner No. 309840.

Note:

Further sizes on request.

External Ø D: 78 mm

Milling mandrel length L₄: 24 mm

Technical description

| | |
|---------------------------------------|---------------|
| Spigot Ø d ₁ | 32 mm |
| External Ø D | 78 mm |
| Milling mandrel length L ₄ | 24 mm |
| Adapter | BT 50 A = 300 |
| Standard | DIN 6357 |

| | |
|---------------------------------------|--------------------|
| Arbor standard | DIN 69882-3 |
| Arbor standard | JIS B6339 |
| Arbor standard | JIS B6339 |
| Shape | A |
| Balance quality G at rotational speed | G 6.3 at 8,000 rpm |
| Concentricity | ≤ 6 μm |
| Machining strategy | HPC |
| Vibration | damped |
| Type of product | Milling head arbor |

Accessories

| | |
|---|-----------|
| Pull-stud 60° sealed suitable for steep tapers 50 | 308780 50 |
| Pull stud 60° sealed suitable for steep tapers 50 | 308785 50 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308790 50 |
| Pull stud 45° sealed suitable for steep tapers 50 | 308760 50 |
| Toggle spanner for mandrel Ø 32 mm | 309840 32 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308795 50 |
| Pull stud 45° sealed suitable for steep tapers 50 | 308765 50 |