



## Short drill chuck Form A, BT 50, Clamping range: 2,5-16 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 303166 2,5-16 |
| GTIN         | 4045197937940 |
| Item class   | 32K           |

### Description

#### Version:

For clockwise and anticlockwise rotation.

- **Slim design.**
- **Specific coolant transfer to tools with IC.**
- **Optimum holding torques at the tool.**

#### Supplied with:

**Clamping wrench.**

#### Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

maximum tightening torque  $M_{d,max} \leq 14$  Nm

Overhang dimension A: 106 mm

External  $\varnothing$  D: 50 mm

Spare Torx® chuck key No. 625220: TX25

### Technical description

|                                  |             |
|----------------------------------|-------------|
| Clamping range                   | 2.5 - 16 mm |
| External $\varnothing$ D         | 50 mm       |
| Overhang dimension A             | 106 mm      |
| Spare Torx® chuck key No. 625220 | TX25        |
| Adapter                          | BT 50       |

|   |                       |
|---|-----------------------|
| Arbor standard                              | ISO 7388-2            |
| Arbor standard                              | JIS B6339             |
| Shape                                       | A                     |
| Balance quality G at rotational speed       | G 6.3 at 12,000 rpm   |
| Concentricity                               | $\leq 50 \mu\text{m}$ |
| maximum tightening torque $M_{d\text{max}}$ | $\leq 14 \text{ Nm}$  |
| Type of product                             | Short drill chuck     |