

Garant
Short drill chuck Form ADB, BT 40, Clamping range: 0,3-10 mm

Order data

Order number	303175 0,3-10
GTIN	4045197868794
Item class	31B

Description
Version:

For clockwise and anticlockwise rotation.

Concentricity $\leq 20 \mu\text{m}$.

With through coolant feed up to max. 50 bar. Max. slim design for the most popular \varnothing up to 10.2 mm.

Supplied with:

Clamping wrench.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 20 \mu\text{m}$

Overhang dimension A: 73 mm

External \varnothing D: 38 mm

Spare chuck key No. 627425: 4 AF

Technical description

Clamping range	0.3 - 10.2 mm
Spare chuck key No. 627425	4 AF
Overhang dimension A	73 mm
External \varnothing D	38 mm
Adapter	BT 40
Arbor standard	JIS B6339

Arbor standard	ISO 7388-2
Shape	ADB
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
Type of product	Short drill chuck

Accessories

Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Hexagon screwdriver with T-handle Hexagon 4 mm	627425 4
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Hexagon screwdriver, with T-handle Hexagon 4 mm	627481 4
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40

Pull stud Hurco 45° with fit sealed suitable for steep tapers
40

308802 40

Torque insert for Pull studs to DIN 69872 suitable for ISO
taper size 40

308810 40

Hurco 60° pull stud with bore and fit sealed suitable for
steep tapers 40

308803 40