

Garant
Short drill chuck Form ADB, BT 50, Clamping range: 0,5-16 mm

Order data

| | |
|--------------|---------------|
| Order number | 303176 0,5-16 |
| GTIN | 4045197584397 |
| Item class | 31B |

Description
Version:

For clockwise and anticlockwise rotation.

Concentricity $\leq 20 \mu\text{m}$.

With through coolant feed up to max. 50 bar.

Supplied with:

Clamping wrench.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 20 \mu\text{m}$

Overhang dimension A: 110 mm

External \varnothing D: 57 mm

Spare chuck key No. 627425: 6 AF

Technical description

| | |
|----------------------------|-------------|
| Overhang dimension A | 110 mm |
| Spare chuck key No. 627425 | 6 AF |
| Clamping range | 0.5 - 16 mm |
| External \varnothing D | 57 mm |
| Adapter | BT 50 |
| Arbor standard | JIS B6339 |
| Arbor standard | ISO 7388-2 |

| | |
|---------------------------------------|-----------------------|
| Shape | ADB |
| Through-coolant | yes, with max. 50 bar |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 20 µm |
| Type of product | Short drill chuck |

Accessories

| | |
|--|-----------|
| Pull stud 45° sealed suitable for steep tapers 50 | 308765 50 |
| Hexagon screwdriver with T-handle Hexagon 6 mm | 627425 6 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308795 50 |
| Pull-stud 60° sealed suitable for steep tapers 50 | 308780 50 |
| Torque insert for Pull studs to SO 7388 suitable for ISO taper size 50 | 308812 50 |
| Hexagon screwdriver, with T-handle Hexagon 6 mm | 627481 6 |
| Pull stud 60° sealed suitable for steep tapers 50 | 308785 50 |
| Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 50 | 308820 50 |
| Pull stud 45° sealed suitable for steep tapers 50 | 308760 50 |
| Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 50 | 308810 50 |
| Pull stud 90° sealed suitable for steep tapers 50 | 308790 50 |