



Short drill chuck Form A, BT 30, Clamping range: 0,5-13 mm



Order data

Order number	303196 0,5-13
GTIN	2050001839022
Item class	33W

Description

Version:

For clockwise and anticlockwise rotation.

Supplied with:

Clamping wrench.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 30 \mu\text{m}$

Overhang dimension A: 96 mm

External \varnothing D: 50 mm

Spare chuck key No. 627425: 6 AF

Technical description

Overhang dimension A	96 mm
Spare chuck key No. 627425	6 AF
Clamping range	0.5 - 13 mm
External \varnothing D	50 mm
Adapter	BT 30
Arbor standard	ISO 7388-2
Arbor standard	JIS B6339
Shape	A

Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 30 μm
Type of product	Short drill chuck

Accessories

Pull stud 45° sealed suitable for steep tapers 30	308760 30
Pull stud 60° sealed suitable for steep tapers 30	308785 30
Hexagon screwdriver, with T-handle Hexagon 4 mm	627481 4
Hexagon screwdriver with T-handle Hexagon 4 mm	627425 4
Pull-stud 60° sealed suitable for steep tapers 30	308780 30
Pull stud 45° sealed suitable for steep tapers 30	308765 30