



Short drill chuck Form A, BT 40, Clamping range: 2,5-16 mm



Order data

Order number	303197 2,5-16
GTIN	2050001701268
Item class	33W

Description

Version:

For clockwise and anticlockwise rotation.

Supplied with:

Clamping wrench.

Optional extras:

Pull studs (PS) No. 308760 – 308806. Pull stud wrenches No. 308820; 308835.

Concentricity: $\leq 30 \mu\text{m}$

Overhang dimension A: 103 mm

External \varnothing D: 57 mm

Spare chuck key No. 627425: 6 AF

Technical description

Clamping range	2.5 - 16 mm
Overhang dimension A	103 mm
Spare chuck key No. 627425	6 AF
External \varnothing D	57 mm
Adapter	BT 40
Arbor standard	JIS B6339
Arbor standard	ISO 7388-2
Shape	A

Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 30 µm
Type of product	Short drill chuck

Accessories

Pull stud 45° sealed suitable for steep tapers 40	308765 40
Pull stud 90° sealed suitable for steep tapers 40	308795 40
Pull stud Hurco 90° with fit sealed suitable for steep tapers 40	308806 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Torque insert for Pull studs to SO 7388 suitable for ISO taper size 40	308812 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Wrench for pull studs DIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Torque insert for Pull studs to DIN 69872 suitable for ISO taper size 40	308810 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Wrench for pull studs ISO 7388 suitable for ISO taper size 40	308830 40
Hexagon screwdriver with T-handle Hexagon 6 mm	627425 6
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
Pull stud 90° sealed suitable for steep tapers 40	308790 40
Pull stud 60° sealed suitable for steep tapers 40	308785 40
Hexagon screwdriver, with T-handle Hexagon 6 mm	627481 6

Pull stud Hurco 45° with fit sealed suitable for steep tapers
40

308802 40