

Garant
Shrink-fit chuck Form ADB, BT 40 short, Clamping range \varnothing D1: 20 mm

Order data

Order number	303410 20
GTIN	4045197467881
Item class	31A

Description
Version:

- Integral tool length adjustment, range 10 mm (from \varnothing 6).
- Size 3-5 for carbide, from size 6 for HSS and carbide.

Application:

For clamping tools with parallel shank to h6 tolerance.

Standard:

Ähnlich E-DIN 69882-8, Form G.

Optional extras:

Pull studs (PS), No. 308760 – 308806, shrink-fit chuck extension No. 302410 – 302417, shrink-fit units No. 354210 – 354400.

Overhang dimension A: 90 mm

External \varnothing D: 42 mm

\varnothing D₂: 33 mm

Technical description

\varnothing D ₂	33 mm
Overhang dimension A	90 mm
Clamping \varnothing D ₁	20 mm
External \varnothing D	42 mm
Adapter	BT 40 short
Arbor standard	ISO 7388-2

Arbor standard	JIS B6339
Shape	ADB
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Shrink-fit chuck

Accessories

Pull stud 60° sealed suitable for steep tapers 40	308785 40
Pull stud 45° sealed suitable for steep tapers 40	308760 40
Cooling adapter short 4.5° for clamping Ø 16,1-22 mm	354235 16,1-22
Pull stud Hurco 90° with bore and fit sealed suitable for steep tapers 40	308805 40
Pull stud Hurco 45° with bore and fit sealed suitable for steep tapers 40	308801 40
Torque insert for Pull studs to SO 7388 suitable for steep tapers 40 SK	308812 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40
Screening plate for coil SU1 for clamping Ø 12-20 mm	354240 12-20
Basic tool mounting for SK for taper shank 40 SK	354225 40
Hurco 60° pull stud with bore and fit sealed suitable for steep tapers 40	308803 40
Shrink-fit unit Type SU1	354210 SU1
Pull stud Hurco 45° with fit sealed suitable for steep tapers 40	308802 40
Pull stud Hurco 60° with fit sealed suitable for steep tapers 40	308804 40
Pull-stud 60° sealed suitable for steep tapers 40	308780 40
	308806 40

Pull stud Hurco 90° with fit sealed suitable for steep tapers 40

Cooling adapter long 4.5° for clamping Ø 16,1-22 mm	354236 16,1-22
---	----------------

Pull stud 90° sealed suitable for steep tapers 40	308790 40
---	-----------

Pull stud 90° sealed suitable for steep tapers 40	308795 40
---	-----------

Torque insert for Pull studs to DIN 69872 suitable for steep tapers 40 SK	308810 40
---	-----------

Subframe cupboard	354290
-------------------	--------

Cooling unit Type CU1	354215 CU1
-----------------------	------------