

Garant

**Side lock arbor Nickel-plated, with cooling channel bore, HSK-A 63 short,
Clamping \varnothing D1: 20 mm**


Order data

| | |
|--------------|---------------|
| Order number | 304272 20 |
| GTIN | 4045197945600 |
| Item class | 31A |

Description
Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

GARANT: All shanks hard turned (for smooth running!).
Special nickel plating.

With **coolant hole bores** tapped for plugging.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 80 mm

External \varnothing D: 52 mm

Spare clamping screw No. 30 9900: 20

Technical description

| | |
|---------------------------------------|-------|
| External \varnothing D | 52 mm |
| Overhang dimension A | 80 mm |
| Clamping \varnothing D ₁ | 20 mm |

| | |
|---------------------------------------|---------------------|
| Spare clamping screw No. 30 9900 | 20 |
| Adapter | HSK-A 63 short |
| Arbor standard | ISO 12164-1 |
| Arbor standard | DIN 69882-4 |
| Arbor standard | DIN 69893 |
| Shape | A |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 3 μm |
| Machining strategy | HSC |
| Machining strategy | HPC |
| Type of product | Side lock arbor |

Accessories

Spare clamping screw for chucks with clamping Ø D1 20 mm

309900 20