



## Side lock arbor, HSK-A 63 short, Clamping range $\varnothing$ D1: 14 mm



### Order data

Order number	304277 14
GTIN	4045197709042
Item class	32A

### Description

#### Version:

- With Balluffchip bore.
- HSK mating faces machined.

#### Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

#### Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

#### Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 80 mm

External  $\varnothing$  D: 44 mm

Spare clamping screw No. 30 9900: 12

### Technical description

Overhang dimension A	80 mm
Clamping $\varnothing$ D <sub>1</sub>	14 mm
Spare clamping screw No. 30 9900	12
External $\varnothing$ D	44 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69893

Arbor standard	DIN 69882-4
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

Spare clamping screw for chucks with clamping Ø D1 12 mm	309900 12
--	-----------