



Side lock arbor, HSK-A 63 short, Clamping range $\varnothing D_1$: 8 mm



Order data

| | |
|--------------|---------------|
| Order number | 304277 8 |
| GTIN | 4045197709011 |
| Item class | 32A |

Description

Version:

- With Balluffchip bore.
- HSK mating faces machined.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 65 mm

External $\varnothing D$: 28 mm

Spare clamping screw No. 30 9900: 8

Technical description

| | |
|----------------------------------|----------------|
| Spare clamping screw No. 30 9900 | 8 |
| Overhang dimension A | 65 mm |
| Clamping $\varnothing D_1$ | 8 mm |
| External $\varnothing D$ | 28 mm |
| Adapter | HSK-A 63 short |
| Arbor standard | DIN 69893 |

| | |
|---------------------------------------|---------------------|
| Arbor standard | DIN 69882-4 |
| Arbor standard | ISO 12164-1 |
| Shape | A |
| Balance quality G at rotational speed | G 6.3 at 20,000 rpm |
| Concentricity | ≤ 3 μm |
| Machining strategy | HSC |
| Machining strategy | HPC |
| Type of product | Side lock arbor |

Accessories

| | |
|---|----------|
| Spare clamping screw for chucks with clamping Ø D1 8 mm | 309900 8 |
|---|----------|