



Side lock arbor with cooling channel bore, HSK-A 63 short, Clamping \varnothing D1: 8 mm



Order data

Order number	304278 8
GTIN	4045197944290
Item class	32A

Description

Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 65 mm

External \varnothing D: 28 mm

Spare clamping screw No. 30 9900: 8

Technical description

External \varnothing D	28 mm
Clamping \varnothing D ₁	8 mm
Overhang dimension A	65 mm
Spare clamping screw No. 30 9900	8
Adapter	HSK-A 63 short

Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-4
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	lockable
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping \varnothing D1 8 mm	309900 8
---	----------