

## Garant

### Side lock arbor with cooling channel bore, HSK-A 63 short, Clamping range Ø D1: 6 mm



#### Order data

Order number	304305 6
GTIN	4045197288882
Item class	31A

#### Description

##### Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

**GARANT:** All shanks hard turned (for smooth cutting action!).

With **coolant hole bores** tapped for plugging.

##### Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

##### Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

##### Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 65 mm

External Ø D: 25 mm

Spare clamping screw No. 30 9900: 6

#### Technical description

Overhang dimension A	65 mm
Spare clamping screw No. 30 9900	6
Clamping Ø D <sub>1</sub>	6 mm
External Ø D	25 mm

Adapter	HSK-A 63 short
Arbor standard	DIN 69893
Arbor standard	DIN 69882-4
Arbor standard	ISO 12164-1
Shape	A
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Side lock arbor

---

## Accessories

Spare clamping screw for chucks with clamping Ø D1 6 mm

309900 6