



Side lock arbor, HSK-A 63 A = 120, Clamping range \varnothing D1: 12 mm



Order data

| | |
|--------------|---------------|
| Order number | 304317 12 |
| GTIN | 4045197709134 |
| Item class | 32A |

Description

Version:

- With Balluffchip bore.
- HSK mating faces machined.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

External \varnothing D: 42 mm

Spare clamping screw No. 30 9900: 12

Technical description

| | |
|---------------------------------------|------------------|
| Clamping \varnothing D ₁ | 12 mm |
| Spare clamping screw No. 30 9900 | 12 |
| External \varnothing D | 42 mm |
| Adapter | HSK-A 63 A = 120 |
| Arbor standard | DIN 69893 |
| Arbor standard | DIN 69882-4 |

| | |
|---------------------------------------|----------------------|
| Arbor standard | ISO 12164-1 |
| Shape | A |
| Balance quality G at rotational speed | G 6.3 at 20,000 rpm |
| Concentricity | $\leq 3 \mu\text{m}$ |
| Machining strategy | HPC |
| Machining strategy | HSC |
| Type of product | Side lock arbor |

Accessories

| | |
|--|-----------|
| Spare clamping screw for chucks with clamping \varnothing D1 12 mm | 309900 12 |
|--|-----------|