


**Side lock arbor, HSK-A 63 A = 120, Clamping range  $\varnothing$  D1: 14 mm**

**Order data**

Order number	304317 14
GTIN	4045197709141
Item class	32A

**Description**
**Version:**

- **With Balluffchip bore.**
- **HSK mating faces machined.**

**Application:**

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

**Optional extras:**

Coolant pipe No. 309880, coolant pipe wrench No. 309890

**Note:**

HSK 40 and 50, Form A and E available ex works by the manufacturer.

External  $\varnothing$  D: 44 mm

Spare clamping screw No. 30 9900: 12

**Technical description**

Clamping $\varnothing$ D <sub>1</sub>	14 mm
Spare clamping screw No. 30 9900	12
External $\varnothing$ D	44 mm
Adapter	HSK-A 63 A = 120
Arbor standard	DIN 69893
Arbor standard	DIN 69882-4

Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HPC
Machining strategy	HSC
Type of product	Side lock arbor

---

## Accessories

Spare clamping screw for chucks with clamping $\varnothing$ D1 12 mm	309900 12
--	-----------