

Garant
Side lock arbor, HSK-A 63 A = 160, Clamping range \varnothing D1: 25 mm

Order data

Order number	304335 25
GTIN	4045197289148
Item class	31A

Description
Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

GARANT: All shanks hard turned (for smooth cutting action!).

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

External \varnothing D: 65 mm

Spare clamping screw No. 30 9900: 25

Technical description

Spare clamping screw No. 30 9900	25
Clamping \varnothing D ₁	25 mm
External \varnothing D	65 mm
Adapter	HSK-A 63 A = 160
Arbor standard	DIN 69893
Arbor standard	DIN 69882-4

Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

HSK coolant tube for HSK 25	309880 25
Socket wrench for coolant tubes for HSK 25	309890 25
Spare clamping screw for chucks with clamping Ø D1 25 mm	309900 25