Garant

Side lock arbor with cooling channel bore, HSK-A 63 A = 160, Clamping \varnothing D1: 10 mm



Order data

Order number	304336 10
GTIN	4045197943330
Item class	31A

Description

Version:

- · With Balluffchip bore.
- · HSK mating faces machined.

GARANT: All shanks hard turned (for smooth running!).

With **coolant hole bores** tapped for plugging.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

External Ø D: 35 mm

Spare clamping screw No. 30 9900: 10

Technical description

Spare clamping screw No. 30 9900	10
External Ø D	35 mm
Clamping Ø D ₁	10 mm
Adapter	HSK-A 63 A = 160

Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-4
Arbor standard	DIN 69893
Shape	Α
Cooling channel bore	lockable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw	for chucks with clamping Ø D1 10)
mm		

309900 10