

Garant
Side lock arbor, HSK-A 100 short, Clamping range Ø D1: 40 mm

Order data

Order number	304390 40
GTIN	4045197762740
Item class	31A

Description
Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

GARANT: All shanks hard turned (for smooth cutting action!).

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 120 mm

External Ø D: 80 mm

Spare clamping screw No. 30 9900: 32

Technical description

Spare clamping screw No. 30 9900	32
External Ø D	80 mm
Overhang dimension A	120 mm
Clamping Ø D ₁	40 mm
Adapter	HSK-A 100 short

Arbor standard	DIN 69893
Arbor standard	DIN 69882-4
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Side lock arbor

Accessories

HSK coolant tube for HSK 40	309880 40
Spare clamping screw for chucks with clamping Ø D1 32 mm	309900 32
Socket wrench for coolant tubes for HSK 40	309890 40