


Garant

**Side lock arbor Nickel-plated, with cooling channel bore, HSK-A 100 short,
Clamping \varnothing D1: 12 mm**



Order data

Order number	304392 12
GTIN	4045197945648
Item class	31A

Description

Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

GARANT: All shanks hard turned (for smooth running!).

Special nickel plating.

With **coolant hole bores** tapped for plugging.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 80 mm

External \varnothing D: 42 mm

Spare clamping screw No. 30 9900: 12

Technical description

External \varnothing D	42 mm
Clamping \varnothing D ₁	12 mm

Spare clamping screw No. 30 9900	12
Overhang dimension A	80 mm
Adapter	HSK-A 100 short
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-4
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

Accessories

Spare clamping screw for chucks with clamping Ø D1 12 mm	309900 12
--	-----------