



Side lock arbor, HSK-A 100 short, Clamping range Ø D1: 32 mm



Order data

Order number	304397 32
GTIN	4045197709271
Item class	32A

Description

Version:

- With Balluffchip bore.
- HSK mating faces machined.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 100 mm

External Ø D: 72 mm

Spare clamping screw No. 30 9900: 32

Technical description

Clamping Ø D ₁	32 mm
Overhang dimension A	100 mm
Spare clamping screw No. 30 9900	32
External Ø D	72 mm
Adapter	HSK-A 100 short
Arbor standard	DIN 69893

Arbor standard	DIN 69882-4
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Side lock arbor

Accessories

HSK coolant tube for HSK 32	309880 32
Spare clamping screw for chucks with clamping Ø D1 32 mm	309900 32
Socket wrench for coolant tubes for HSK 32	309890 32