

HOLEX
Side lock arbor with cooling channel bore, HSK-A 100 short, Clamping \varnothing D1: 10 mm

Order data

| | |
|--------------|---------------|
| Order number | 304398 10 |
| GTIN | 4045197944405 |
| Item class | 32A |

Description
Version:

- With Balluffchip bore.
- HSK mating faces machined.

Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 80 mm

External \varnothing D: 35 mm

Spare clamping screw No. 30 9900: 10

Technical description

| | |
|---------------------------------------|-------|
| Overhang dimension A | 80 mm |
| External \varnothing D | 35 mm |
| Spare clamping screw No. 30 9900 | 10 |
| Clamping \varnothing D ₁ | 10 mm |

| | |
|---------------------------------------|----------------------|
| Adapter | HSK-A 100 short |
| Arbor standard | ISO 12164-1 |
| Arbor standard | DIN 69882-4 |
| Arbor standard | DIN 69893 |
| Shape | A |
| Cooling channel bore | lockable |
| Balance quality G at rotational speed | G 6.3 at 20,000 rpm |
| Concentricity | $\leq 3 \mu\text{m}$ |
| Machining strategy | HSC |
| Machining strategy | HPC |
| Type of product | Side lock arbor |

Accessories

Spare clamping screw for chucks with clamping \varnothing D1 10 mm

309900 10