

## Garant

**Side lock arbor with cooling channel bore, HSK-A 100 short, Clamping range  
Ø D1: 25 mm**



### Order data

Order number	304402 25
GTIN	4045197289346
Item class	31A

### Description

#### Version:

- **With Balluffchip bore.**
- **HSK mating faces machined.**

**GARANT:** All shanks hard turned (for smooth cutting action!).

With **coolant hole bores** tapped for plugging.

#### Application:

For clamping tools with Weldon shank to DIN 1835 Form B and DIN 6535 Form HB.

#### Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

#### Note:

HSK 40 and 50, Form A and E available ex works by the manufacturer.

Overhang dimension A: 100 mm

External Ø D: 65 mm

Spare clamping screw No. 30 9900: 25

### Technical description

Clamping Ø D <sub>1</sub>	25 mm
Overhang dimension A	100 mm
Spare clamping screw No. 30 9900	25
External Ø D	65 mm

Adapter	HSK-A 100 short
Arbor standard	DIN 69893
Arbor standard	DIN 69882-4
Arbor standard	ISO 12164-1
Shape	A
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor

---

## Accessories

HSK coolant tube for HSK 100	309880 100
Spare clamping screw for chucks with clamping Ø D1 25 mm	309900 25