

Garant

Combination side lock arbor, slim, HSK-A 63 A = 160, Clamping range \varnothing D1: 20 mm


Order data

Order number	304715 20
GTIN	4045197289612
Item class	31A

Description
Version:

- With ball-jointed clamping screw for Weldon and Whistle-Notch systems (clamping flat inclination 2°).
- With Balluffchip bore.
- All shanks hard turned (for smooth running!).
- SK mating faces machined.

Application:

For clamping tools with parallel shank to DIN 1835 Form B + E and DIN 6535 Form HB + HE.

Supplied with:

Ball-jointed clamping screw and through-drilled back stop screw.

Optional extras:

Coolant pipe No. 309880, coolant pipe wrench No. 309890

External \varnothing D: 38 mm

\varnothing D₂: 25 mm

\varnothing D₃: 30 mm

Reach L₁: 129 mm

Technical description

Reach L ₁	129 mm
Clamping \varnothing D ₁	20 mm
\varnothing D ₃	30 mm

Ø D ₂	25 mm
External Ø D	38 mm
Adapter	HSK-A 63 A = 160
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Machining strategy	HPC
Type of product	Side lock arbor