


**ER collet chuck, HSK-A 63 A = 160, for ER collet size: 40 ER**

**Order data**

Order number	305439 40
GTIN	4045197953797
Item class	32A

**Description**
**Version:**

- **All shanks hard turned (for smooth running!).**
- **Through bored (without adjustment screw).**
- **HSK mating faces machined.**

With Balluffchip bore.

**Application:**

For clamping tools with plain shanks in ER collets to DIN 6499 – Form A and B.

**Supplied with:**

Coated High-Speed clamping nut.

**Optional extras:**

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, ER collets No. 308881 – 309434, ER chuck key No. 309680 or 613300.

Clamping range: 3 - 26 mm

External Ø D: 63 mm

**Technical description**

External Ø D	63 mm
Clamping range	3 - 26 mm
for ER collets	40
Adapter	HSK-A 63 A = 160
Arbor standard	ISO 12164-1

Arbor standard	DIN 69893
Arbor standard	DIN 69882-6
Shape	A
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	≤ 3 μm
Machining strategy	HSC
Balluffchip bore	yes
Type of product	Collet chuck

---

## Accessories

ER chuck key for ER collet chuck 40	309680 40
-------------------------------------	-----------