

**Garant**
**Face mill arbor, HSK-A 63 short, Spigot  $\varnothing$  d1: 16 mm**

**Order data**

Order number	306510 16
GTIN	4045197290120
Item class	31A

**Description**
**Version:**

- Spigot  $\varnothing$  40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

**Application:**

For clamping shell end mills and milling cutter heads.

**Supplied with:**

Lock screw

**Optional extras:**

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External  $\varnothing$  D: 38 mm

Milling mandrel length  $L_4$ : 17 mm

Spare milling cutter lock screw No. 309860: 16

**Technical description**

Spigot $\varnothing$ d <sub>1</sub>	16 mm
Overhang dimension A	50 mm
Spare milling cutter lock screw No. 309860	16
Milling mandrel length $L_4$	17 mm

Suitable toggle spanner No. 309840	16
External Ø D	38 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

---

## Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
Milling cutter lock screw for mandrel Ø 16 mm	309860 16