

Garant
Face mill arbor, HSK-A 63 short, Spigot \varnothing d1: 40 mm

Order data

Order number	306510 40
GTIN	4045197656810
Item class	31A

Description
Version:

- Spigot \varnothing 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 60 mm

External \varnothing D: 88 mm

Milling mandrel length L_4 : 27 mm

Spare milling cutter lock screw No. 309860: 40

Technical description

Overhang dimension A	60 mm
Spare milling cutter lock screw No. 309860	40
Spigot \varnothing d ₁	40 mm
Milling mandrel length L_4	27 mm

Suitable toggle spanner No. 309840	40
External Ø D	88 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 40 mm	309840 40
Milling cutter lock screw for mandrel Ø 40 mm	309860 40