

Garant
Face mill arbor with cooling channel bore, HSK-A 63 short, Spigot Ø d1: 16 mm

Order data

| | |
|--------------|---------------|
| Order number | 306530 16 |
| GTIN | 4045197290168 |
| Item class | 31A |

Description
Version:

- **Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External Ø D: 38 mm

Milling mandrel length L₄: 17 mm

Spare milling cutter lock screw No. 309860: 16

Technical description

| | |
|--|----|
| Suitable toggle spanner No. 309840 | 16 |
| Spare milling cutter lock screw No. 309860 | 16 |

| | |
|---------------------------------------|---------------------|
| Overhang dimension A | 50 mm |
| Milling mandrel length L ₄ | 17 mm |
| Spigot Ø d ₁ | 16 mm |
| External Ø D | 38 mm |
| Adapter | HSK-A 63 short |
| Arbor standard | DIN 69882-3 |
| Arbor standard | ISO 12164-1 |
| Arbor standard | DIN 69893 |
| Shape | A |
| Cooling channel bore | not pluggable |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 6 µm |
| Machining strategy | HPC |
| Type of product | Milling head arbor |

Accessories

| | |
|---|-----------|
| Toggle spanner for mandrel Ø 16 mm | 309840 16 |
| Milling cutter lock screw for mandrel Ø 16 mm | 309860 16 |