

Garant
Face mill arbor with cooling channel bore, HSK-A 63 short, Spigot Ø d1: 32 mm

Order data

Order number	306530 32
GTIN	4045197290199
Item class	31A

Description
Version:

- **Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 60 mm

External Ø D: 78 mm

Milling mandrel length L₄: 24 mm

Spare milling cutter lock screw No. 309860: 32

Technical description

Spigot Ø d ₁	32 mm
Suitable toggle spanner No. 309840	32

Overhang dimension A	60 mm
Spare milling cutter lock screw No. 309860	32
Milling mandrel length L ₄	24 mm
External Ø D	78 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Milling cutter lock screw for mandrel Ø 32 mm	309860 32
Toggle spanner for mandrel Ø 32 mm	309840 32