


Garant
Face mill arbor with cooling channel bore, HSK-F 63 short, Spigot Ø d1: 16 mm

Order data

Order number	306531 16
GTIN	4045197587800
Item class	31A

Description
Version:

- **Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 45 mm

External Ø D: 38 mm

Milling mandrel length L₄: 17 mm

Spare milling cutter lock screw No. 309860: 16

Technical description

Spigot Ø d ₁	16 mm
Milling mandrel length L ₄	17 mm

Suitable toggle spanner No. 309840	16
Spare milling cutter lock screw No. 309860	16
Overhang dimension A	45 mm
External Ø D	38 mm
Adapter	HSK-F 63 short
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	F
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Milling cutter lock screw for mandrel Ø 16 mm	309860 16
Toggle spanner for mandrel Ø 16 mm	309840 16