

Garant
Face mill arbor with cooling channel bore, HSK-F 63 short, Spigot Ø d1: 40 mm

Order data

Order number	306531 40
GTIN	4045197587848
Item class	31A

Description
Version:

- **Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 65 mm

External Ø D: 88 mm

Milling mandrel length L₄: 27 mm

Spare milling cutter lock screw No. 309860: 40

Technical description

Milling mandrel length L ₄	27 mm
Suitable toggle spanner No. 309840	40

Overhang dimension A	65 mm
Spigot $\varnothing d_1$	40 mm
Spare milling cutter lock screw No. 309860	40
External $\varnothing D$	88 mm
Adapter	HSK-F 63 short
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	F
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 6 \mu\text{m}$
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Milling cutter lock screw for mandrel $\varnothing 40$ mm	309860 40
Toggle spanner for mandrel $\varnothing 40$ mm	309840 40