



## Face mill arbor with cooling channel bore, HSK-A 63 short, Spigot Ø d1: 16 mm



### Order data

Order number	306537 16
GTIN	4045197712257
Item class	32A

### Description

#### Version:

- Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

With **cooling channel bores.**

#### Application:

For clamping shell end mills and milling cutter heads.

#### Supplied with:

Lock screw

#### Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 50 mm

External Ø D: 35 mm

Milling mandrel length L<sub>4</sub>: 17 mm

Spare milling cutter lock screw No. 309860: 16

### Technical description

Suitable toggle spanner No. 309840	16
Spigot Ø d <sub>1</sub>	16 mm

Spare milling cutter lock screw No. 309860	16
Milling mandrel length L <sub>4</sub>	17 mm
Overhang dimension A	50 mm
External Ø D	35 mm
Adapter	HSK-A 63 short
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 6.3 at 20,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

## Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
Milling cutter lock screw for mandrel Ø 16 mm	309860 16