

HOLEX

Face mill arbor with cooling channel bore, HSK-A 63 short, Spigot Ø d1: 40 mm



Order data

| | |
|--------------|---------------|
| Order number | 306537 40 |
| GTIN | 4045197712295 |
| Item class | 32A |

Description

Version:

- Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 60 mm

External Ø D: 88 mm

Milling mandrel length L₄: 27 mm

Spare milling cutter lock screw No. 309860: 40

Technical description

| | |
|--|-------|
| Milling mandrel length L ₄ | 27 mm |
| Spare milling cutter lock screw No. 309860 | 40 |

| | |
|---------------------------------------|---------------------|
| Suitable toggle spanner No. 309840 | 40 |
| Spigot Ø d ₁ | 40 mm |
| Overhang dimension A | 60 mm |
| External Ø D | 88 mm |
| Adapter | HSK-A 63 short |
| Arbor standard | DIN 69882-3 |
| Arbor standard | ISO 12164-1 |
| Arbor standard | DIN 69893 |
| Shape | A |
| Cooling channel bore | not pluggable |
| Balance quality G at rotational speed | G 6.3 at 20,000 rpm |
| Concentricity | ≤ 6 µm |
| Machining strategy | HPC |
| Type of product | Milling head arbor |

Accessories

| | |
|---|-----------|
| Milling cutter lock screw for mandrel Ø 40 mm | 309860 40 |
| Toggle spanner for mandrel Ø 40 mm | 309840 40 |