

## Garant

**Face mill arbor with cooling channel bore, HSK-A 63 medium, Spigot Ø d1: 16 mm**



### Order data

Order number	306541 16
GTIN	4045197763532
Item class	31A

### Description

#### Version:

- Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

With **cooling channel bore**.

#### Application:

For clamping shell end mills and milling cutter heads.

#### Supplied with:

Lock screw

#### Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 75 mm

External Ø D: 38 mm

Milling mandrel length L<sub>4</sub>: 17 mm

Spare milling cutter lock screw No. 309860: 16

### Technical description

Overhang dimension A	75 mm
Spigot Ø d <sub>1</sub>	16 mm

External Ø D	38 mm
Spare milling cutter lock screw No. 309860	16
Milling mandrel length L <sub>4</sub>	17 mm
Suitable toggle spanner No. 309840	16
Adapter	HSK-A 63 medium
Arbor standard	DIN 69893
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Shape	A
Cooling channel bore	cannot be plugged
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

## Accessories

Toggle spanner for mandrel Ø 16 mm	309840 16
Milling cutter lock screw for mandrel Ø 16 mm	309860 16