

Garant
Face mill arbor with cooling channel bore, HSK-A 63 medium, Spigot Ø d1: 32 mm

Order data

Order number	306541 32
GTIN	4045197763563
Item class	31A

Description
Version:

- Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

With **cooling channel bore**.

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant pipe No. 309880, Plug-in socket No. 309890, Special toggle spanner No. 309840.

Overhang dimension A: 80 mm

External Ø D: 78 mm

Milling mandrel length L₄: 24 mm

Spare milling cutter lock screw No. 309860: 32

Technical description

Overhang dimension A	80 mm
External Ø D	78 mm

Suitable toggle spanner No. 309840	32
Spigot $\varnothing d_1$	32 mm
Milling mandrel length L_4	24 mm
Spare milling cutter lock screw No. 309860	32
Adapter	HSK-A 63 medium
Arbor standard	DIN 69893
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Shape	A
Cooling channel bore	cannot be plugged
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 6 \mu\text{m}$
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel $\varnothing 32$ mm	309840 32
Milling cutter lock screw for mandrel $\varnothing 32$ mm	309860 32