

**Garant**
**Face mill arbor with cooling channel bore, HSK-A 63 A = 130, Spigot Ø d1: 16 mm**

**Order data**

Order number	306566 16
GTIN	4045197870162
Item class	31A

**Description**
**Version:**

- **Clamping Ø 40 with 4 tapped holes for drive blocks to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

**Application:**

For clamping shell end mills and milling cutter heads.

**Supplied with:**

Lock screw.

**Optional extras:**

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, toggle spanner No. 309840.

External Ø D: 38 mm

Milling mandrel length L<sub>4</sub>: 17 mm

Spare milling cutter lock screw No. 309860: 16

**Technical description**

Spigot Ø d <sub>1</sub>	16 mm
Suitable toggle spanner No. 309840	16
External Ø D	38 mm
Spare milling cutter lock screw No. 309860	16

Milling mandrel length L <sub>4</sub>	17 mm
Adapter	HSK-A 63 A = 130
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 μm
Machining strategy	HPC
Type of product	Milling head arbor

---

## Accessories

Milling cutter lock screw for mandrel Ø 16 mm	309860 16
Toggle spanner for mandrel Ø 16 mm	309840 16