

Garant
Face mill arbor with cooling channel bore, HSK-A 100 short, Spigot \varnothing d1: 50 mm

Order data

Order number	306675 50
GTIN	4045197290397
Item class	31A

Description
Version:

- Spigot \varnothing 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

With **cooling channel bores.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, toggle spanner No. 309840.

Overhang dimension A: 70 mm

External \varnothing D: 120 mm

Milling mandrel length L_4 : 30 mm

Spare milling cutter lock screw No. 309860: 50

Technical description

Milling mandrel length L_4	30 mm
------------------------------	-------

Suitable toggle spanner No. 309840	50
Spigot Ø d ₁	50 mm
Spare milling cutter lock screw No. 309860	50
Overhang dimension A	70 mm
External Ø D	120 mm
Adapter	HSK-A 100 short
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

HSK coolant tube for HSK 50	309880 50
Socket wrench for coolant tubes for HSK 50	309890 50
Milling cutter lock screw for mandrel Ø 50 mm	309860 50