

**Garant**
**Face mill arbor, HSK-A 100 A = 100, Spigot Ø d1: 16 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 306678 16     |
| GTIN         | 4045197290403 |
| Item class   | 31A           |

**Description**
**Version:**

- Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.
- With Balluffchip bore.
- Increased collar contact surface.
- HSK mating faces machined.

**Application:**

For clamping shell end mills and milling cutter heads.

**Supplied with:**

Lock screw

**Optional extras:**

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, toggle spanner No. 309840.

External Ø D: 38 mm

Milling mandrel length L<sub>4</sub>: 17 mm

Spare milling cutter lock screw No. 309860: 16

**Technical description**

|  |       |
|--|-------|
| Suitable toggle spanner No. 309840         | 16    |
| Milling mandrel length L <sub>4</sub>      | 17 mm |
| Spare milling cutter lock screw No. 309860 | 16    |
| Spigot Ø d <sub>1</sub>                    | 16 mm |

|                                       |                     |
|---------------------------------------|---------------------|
| External Ø D                          | 38 mm               |
| Adapter                               | HSK-A 100 A = 100   |
| Arbor standard                        | DIN 69882-3         |
| Arbor standard                        | ISO 12164-1         |
| Arbor standard                        | DIN 69893           |
| Shape                                 | A                   |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity                         | ≤ 6 µm              |
| Machining strategy                    | HPC                 |
| Type of product                       | Milling head arbor  |

---

## Accessories

|   |           |
|---|-----------|
| Toggle spanner for mandrel Ø 16 mm            | 309840 16 |
| Milling cutter lock screw for mandrel Ø 16 mm | 309860 16 |