

Garant
Face mill arbor, HSK-A 100 A = 100, Spigot Ø d1: 50 mm

Order data

Order number	306678 50
GTIN	4045197290458
Item class	31A

Description
Version:

- **Spigot Ø 40 with 4 tapped holes for face mills to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

Application:

For clamping shell end mills and milling cutter heads.

Supplied with:

Lock screw

Optional extras:

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, toggle spanner No. 309840.

External Ø D: 120 mm

Milling mandrel length L_4 : 30 mm

Spare milling cutter lock screw No. 309860: 50

Technical description

Spigot Ø d ₁	50 mm
Suitable toggle spanner No. 309840	50
Spare milling cutter lock screw No. 309860	50
Milling mandrel length L_4	30 mm

External Ø D	120 mm
Adapter	HSK-A 100 A = 100
Arbor standard	DIN 69882-3
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Milling cutter lock screw for mandrel Ø 50 mm	309860 50
HSK coolant tube for HSK 50	309880 50
Socket wrench for coolant tubes for HSK 50	309890 50