

**Garant**

**Face mill arbor vibration-damped, cylindrical, with cooling channel bore, HSK-A 100 A = 300, Spigot Ø d1: 22 mm**


**Order data**

Order number	306715 22
GTIN	4045197942630
Item class	31A

**Description**
**Version:**

- **Shank, spigot, and all contact surfaces are ground at the collar.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**

**Vibration damped version, arbor with vibration-damping core.**

**Advantage:**

Significantly lower tendency to vibrate. Considerable increase in feed rate.

**Supplied with:**

Cutter lock screw and drive dog.

**Optional extras:**

Special coolant pipe wrench No. 309840, coolant pipe No. 309880.

**Note:**

Further sizes on request.

Ø D<sub>2</sub>: 48 mm

Milling mandrel length L<sub>4</sub>: 19 mm

**Technical description**

Milling mandrel length L <sub>4</sub>	19 mm
Ø D <sub>2</sub>	48 mm
Spigot Ø d <sub>1</sub>	22 mm
Adapter	HSK-A 100 A = 300
Standard	DIN 6357

Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 6.3 at 8,000 rpm
Concentricity	≤ 6 μm
Machining strategy	HPC
Vibration	damped
Type of product	Milling head arbor