

Garant
Hydraulic clamping chuck short, slim, HSK-A 63, Clamping range \varnothing D1: 6 mm

Order data

| | |
|--------------|---------------|
| Order number | 307512 6 |
| GTIN | 4045197506252 |
| Item class | 31A |

Description
Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

Application:

- For drilling, reaming, and milling.

Optional extras:

Reducer sleeves No. 302135 – 302180, coolant tube No. 309880, coolant tube socket wrench No. 309890, parallel wipers No. 343720.

Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 70 mm

\varnothing D₂: 26 mm

External \varnothing D: 50 mm

L₃: 24 mm

Adjustment travel V: 10 mm

Thread M: M5

Technical description

| | |
|------------------------------|-------|
| \varnothing D ₂ | 26 mm |
| Overhang dimension A | 70 mm |
| Thread M | M5 |

| | |
|---------------------------------------|--------------------------|
| L ₃ | 24 mm |
| Clamping Ø D ₁ | 6 mm |
| External Ø D | 50 mm |
| Adjustment travel V | 10 mm |
| Adapter | HSK-A 63 |
| Arbor standard | DIN 69893 |
| Arbor standard | ISO 12164-1 |
| Arbor standard | DIN 69882-7 |
| Shape | A |
| Through-coolant | yes, with max. 80 bar |
| Balance quality G at rotational speed | G 2.5 at 25,000 rpm |
| Concentricity | ≤ 3 µm |
| Machining strategy | HSC |
| Type of product | Hydraulic clamping chuck |

Accessories

| | |
|-----------------------------------|----------|
| Parallel wiper Plastic Pin Ø 6 mm | 343720 6 |
|-----------------------------------|----------|