



## Hydraulic clamping chuck radial adjustment, HSK-A 63, Clamping range $\varnothing$ D1: 12 mm



### Order data

Order number	307514 12
GTIN	2050001700940
Item class	33W

### Description

#### Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

With radial adjustment for tool length.

#### Application:

- For drilling, reaming, and milling.

#### Optional extras:

Reducer sleeves No. 302135 – 302180, coolant tube No. 309880, coolant tube socket wrench No. 309890, parallel wipers No. 343720.

WTE stop screws for direct clamping and for use of reducing sleeves on request.

#### Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 90 mm

External  $\varnothing$  D: 50 mm

Adjustment travel V: 10 mm

suitable reducing adapter: 302135; 302140

### Technical description

Overhang dimension A	90 mm
suitable reducing adapter	302135; 302140
Clamping $\varnothing$ D <sub>1</sub>	12 mm

External Ø D	50 mm
Adjustment travel V	10 mm
Adapter	HSK-A 63
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Shape	A
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

## Accessories

Slotted reducing adapter Clamping range Ø D1 3 mm	302135 3
Slotted reducing adapter Clamping range Ø D1 6 mm	302140 6
Slotted reducing adapter Clamping range Ø D1 8 mm	302135 8
Slotted reducing adapter Clamping range Ø D1 4 mm	302140 4
Slotted reducing adapter Clamping range Ø D1 5 mm	302140 5
Parallel wiper Plastic Pin Ø 12 mm	343720 12
Slotted reducing adapter Clamping range Ø D1 3 mm	302140 3
Slotted reducing adapter Clamping range Ø D1 5 mm	302135 5
Slotted reducing adapter Clamping range Ø D1 8 mm	302140 8
Slotted reducing adapter Clamping range Ø D1 4 mm	302135 4
Slotted reducing adapter Clamping range Ø D1 6 mm	302135 6