



Hydraulic clamping chuck short, slim, HSK-A 100, Clamping range Ø D1: 6 mm



Order data

Order number	307525 6
GTIN	2050001653482
Item class	33W

Description

Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

Application:

- For drilling, reaming, and milling.

Optional extras:

Reducer sleeves No. 302135 – 302180, Coolant pipe No. 309880, Coolant pipe wrench No. 309890, Parallel wipers No. 343720.

WTE stop screws for direct clamping and for use of reducing sleeves on request.

Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 75 mm

Ø D₂: 26 mm

External Ø D: 50 mm

L₃: 24 mm

Adjustment travel V: 10 mm

Thread M: M5

Technical description

Thread M	M5
----------	----

L ₃	24 mm
Overhang dimension A	75 mm
Ø D ₂	26 mm
Clamping Ø D ₁	6 mm
External Ø D	50 mm
Adjustment travel V	10 mm
Adapter	HSK-A 100
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Shape	A
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

Accessories

Parallel wiper Plastic Pin Ø 6 mm	343720 6
-----------------------------------	----------